

The **Enhanced Bolt Release** (EBR-M) is designed for use with Mossberg 930/935 shotguns to enlarge the bolt release surface for faster port loads in competition.

BEFORE YOU BEGIN:

Make absolutely sure that your shotgun is unloaded before installation of the EBR. Ensure there are no rounds in the magazine tube and that the chamber has been visually inspected to make sure it is clear. Ensure the bolt is closed as well.

INSTALLATION:

The EBR installs directly over the existing factory bolt release button. Your OEM button should be clean and free of debris before installation of the EBR.

Seat the Enhanced Bolt Release over the factory bolt release button, orienting the set screw toward the bottom of the shotgun. Apply even pressure to the top of the EBR while hand-tightening the set screw with the included key.

Once you have tested the part for proper function and are satisfied with position, you can disassemble the part, apply a drop of blue thread locking compound to the EBR's threads and reassemble. Hand-tighten with key. Do NOT over tighten!

MAINTENANCE:

After the first 100 rounds, check that the Enhanced Bolt Release hasn't rotated or otherwise moved. Finish wear may develop in areas that come in contact with the receiver. This is normal and will not affect function of the EBR or shotgun.

Refer to our website for any updates to installation or maintenance procedures.



www.OR3GUN.com

Made in the USA